

VIKING ACCESS SYSTEMS™

EFFICIENT TECHNOLOGY IN SLIDE GATE OPERATION



L3

residential and commercial


SLIDE GATE OPERATOR

Class I, Class II, Class III, and Class IV Vehicular Gate Operator




L-3™ PRODUCT INFORMATION AND SPECIFICATIONS


The L-3™ gate operator has the capacity to operate slide gates up to 1200 lbs. and 40 feet in length at 100% duty cycle under extreme conditions. It's efficient mechanism provides a solution for high traffic commercial slide gate applications. The Viking L-3™ gate operator offers efficiency and technology combined in a single package.




On-board lightning protection



Innovative Fine Tune Adjustment for the end of gate travel (down to 1/8")



Soft-stop - Soft-start with Intelligent Obstruction Detection



Standard loop rack



Built in optional auto-open feature in case of power failure

120/220 VAC single phase power source

Back-driveable unit features direct drive mechanism

Fail-Safe / Fail-Secure



Operational Voltage	... 24 VDC with 1/2 H.P. Motor
Main Power Source	... 120 / 220 VAC Single Phase
Battery	... 7 AmpHr 12 VDC x 2
Max Gate Capacity	... 1200 lbs. 40'
Max Operating Speed	... 12" per second
Battery Backup Operation	... 100 Full Cycles (1000 lbs. / 20' gate)
Max Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 4° F to + 158° F



800.908.0884
vikingaccess.com

7 YEAR RESIDENTIAL / 5 YEAR COMMERCIAL WARRANTY